Media Technology & Solutions Pvt. Ltd.

Inventory Catalogue

Email: info@sslmediatech.com | Tel: 022-23811823 | Mob: +91- 9820022984

HYL 5R Sharpy

The Litelees 5R Sharpy is a powerful and versatile beam light suitable for both indoor and outdoor events. Equipped with a 5R Philip Platinum Lamp, the SSL 5R Sharpy boasts a dazzling color temperature of 8000K, ensuring captivating and vibrant lighting displays. Its electronic ballast ensures reliable performance and smooth operation, making it a reliable choice for dynamic lighting effects.

With an HQ glass lens and zoom capabilities from zero to 3.8, this fixture offers precise control over its 16 channels, providing endless creative possibilities. The color wheel features 14 colors with adjustable rotation speed, double direction stream, and a rainbow effect, creating stunning color displays.

000

001

With advanced features like the fixed gobo wheel with 17 gobos and open, 8-facet rotating prism, and frost effect, the SSL 5R Sharpy adds depth and dimension to your lighting designs. Its high-temperature protection and Pan/Tilt fine function Auto Correction ensure stability and accuracy in any setup.

Embrace the power and versatility of the SSL's 5R Sharpy for unforgettable lighting experiences, whether it's an indoor concert, outdoor event, or any other occasion that demands exceptional lighting effects.



Technical Specifications

Parameter	Specification
Voltage	AC110-240V 50-60Hz
Power consumption	300W 220V, 50Hz
Light source	5R Philip Platinum Lamp
Color temperature	8000K
Ballast	Electronics ballast
Optics	HQ glass lens
Zoom	From zero to 3.8
Channels	16 channel
Color Wheel	One With 14 Colors + open With adjustable rotation speed With double direction stream and rainbow effect With color location
Fixed Gobo Wheel	With 17 Gobos + open With double direction rotation With sharking effect With adjustable rotating speed
Prism	8 facet rotating prism
Frost	With frost effect
Strobe	Mechanical strobe 1-12 F.P.S. With adjustable strobe speed
Movement	Pan0-540/Tilt 0-270 With Pan/Tilt fine function Auto Correction function
LCD display	High temperature protection
Dimension	44X39X53 Cm
Gross weight	25KG