



Media Technology & Solutions Pvt. Ltd.

# Inventory Catalogue

Email: [info@sslmediatech.com](mailto:info@sslmediatech.com) | Tel: 022-23811823 | Mob: +91- 9820022984





## HYL Apex BSW 5R

Discover the remarkable capabilities of the HYL Apex BSW 5R, a compact yet powerful luminaire that seamlessly merges beam, spot, and wash functionalities into a single, high-performance unit. Equipped with the renowned Philips™ MSD Silver 200W lamp, this fixture delivers unmatched performance.

In beam mode, the HYL Apex BSW 5R astounds with its sharp and defined output, creating a lasting impact. With a motorized zoom range of 2° to 20°, it excels as a beam light, offering captivating and focused illumination for your indoor events.

As a spot luminaire, the HYL Apex BSW 5R impresses with its expansive light beam projection, leaving a striking visual impression. Featuring an array of 13 vibrant colors, 9 rotating gobos, and 12 static gobos, the creative possibilities are limitless.

Furthermore, the HYL Apex BSW 5R excels in wash mode, delivering a seamless and uniform wash effect. The dedicated frost filter enhances wash performance, introducing captivating and dynamic color macro effects.

Designed to excel in any lighting arrangement, whether for concerts, theaters, or live events, the HYL Apex BSW 5R's adaptability and compact size make it the perfect companion for indoor events. Empower lighting designers with the tools to craft immersive and captivating visual experiences.



## Technical Specifications

Parameter	Specification
Voltage	200W-240V/50-60Hz (100-120V/50-60Hz)
Lamp	Philips 200W Average Lifespan: 2000Hrs
Color	13 color + blank color wheel
Gobo	2 Gobo wheels 14 fixed gobo + 9 rotation bobo
Prism	2 Prisms
Prism1 Prism2	6 facet prism in both directions at different speeds one 8 facet prism in both directions at different speeds
Lens	High precision optical lens wash effect adjustable wash effects angle
Focus	Linear adjustment
Dimension	0-100% linear adjustment
ZOOM	Parallel beam angel 2°-20° change
Frost effect	Separate, Variable
Pan/Tilt	X axis 540° and Y axis 250° automatically accurate positioning strobe double lens strobe (0.5-9 times/second)
Control Mode	Jog Shutter selection standard DMX512 Automatic and Master slave mode
DMX Channel	24Ch Mode 1 Lamp on/Off function using DMX
Weight	16.5 Kg
Dimension	390MM X 420MM X 600MM