Media Technology & Solutions Pvt. Ltd.

Inventory Catalogue

Email: info@sslmediatech.com | Tel: 022-23811823 | Mob: +91- 9820022984

SSL Big Eye LED Wash

The SSL Big Eye's moving body, driven by two stepper motors, delivers smooth and precise movements. Enjoy automatic repositioning of PAN & TILT after accidental movement, simplifying setup.

Embrace the innovation of SSL Big Eye and take your lighting design to the next level. The SSL Big Eye, with Osram Ostar RGBW 19x15w LEDs, offers an adjustable color temperature range of 2500K-8000K, ensuring breathtaking visual effects for any event.

Its advanced optics provide a zoom angle from 4° to 60°, catering to various lighting setups. Switch between three operating modes - wash, beam, and FX (Kaleido effects) - to create mesmerizing lighting compositions. The bi-directional continuous rotation of the front lens adds dynamic flair, while the digital Wah-Beam Framing effect and beam edge softening control enhance output.

Experience precise control with a 1-100% linear electronic dimmer and adjustable speed strobe effect. The dedicated channel for color temperature setting and RGBW auto-tuning ensure seamless color adjustments.




Technical Specifications

Specification	Details				
Power Supply	Voltage: 110-240V 50/60 HZ				
Light Source	Osram Ostar RGBW 19x15w LEDs				
Color Toronoroturo	2500K-8000K adjustable				
Color Temperature	Dedicated channel for color temperature setting				
Average life	50,000 H				
Optics	Special Pods: 5 cm x 19 pcs convey the light output of each led to the quadrangle lens, internal light dissipation is decreased, color mixing and the light output are enhanced.				
	19pcs in total with 4 different shapes: 1 sexangle, 6 pentagons, 6 quadrangles, and 6 opposite quadrangles				
Zoom Angle	40-60°				
Dimmer	0-100% linear electronic dimmer				
Strobe	Adjustable speed stop/strobe effect, with instantaneous blackout				
	Uniform wash: no dark spot in the middle benefit from its perfect optic and Invisible front grid.				
	Mid-air parallel beam, when the beam is zoomed down to 4°, the wash light turns into a "Beam" Fixture.				
Effects Section	Spectacular graphic effects, Rotation version brings a new never-seen-before feature, the front lens may be rotated with "vortex" and "kaleidoscope" effects.				
	Variable Built-in Dynamic effects: Each LED can be controlled individually, shape speed shape offset, shape fade, and background select are available.				



Control and Programming	5 channel models				
Display:	LCD display with 5 operating buttons				
Pan/Tilt Resolution	16 bits				
DMX signal connection	3pin and 5pin in & out				
Power connection	PowerCON in & out				
Cooling	High efficiency die-cast aluminum, forced ventilation				
	6 stepper motors, 1 for rotation, 3 for zooming, and 2 for XY, operating with micro steps, totally microprocessor controlled				
Moving Body	Movement by means of 3 phase stepper motors, controlled by microprocessor.				
	Automatic re-position of pan and tilt after accidenta movement not controlled by microprocessor.				
Travel	PAN = 540°, TILT=210°				
Weight	15KG				


Dimensions





Amazing Beam

Perfect Wash



Spectacular Effects

Delicate Graphics



SSL Media Technology & Solutions Inventory Catalogue



Photometrics

R G B W RGBW	(Lu) (Lu) (Lu)	(Lux) (Lux) (Lux) (Lux) (Lux)		2 86 8 92 04	2882 5742 947 6222 14160		740 1348 206 1438 3401	
					=0)	_(4°
Distance (m) Diameter (m)		-	3 0.46		5 1.0		10 2. 0	
R G B W RGBW	(Lux) (Lux) (Lux) (Lux)		283 514 86 577 1345		104 193 44 234 503		36 59 12 61 132	
								°0%
Distand Diamet)	3 2. 1	1	5 3.	2		0 . 6